



SOFTWARE UPGRADE PROCEDURE

MODEL NUMBER	D3045
REFERENCE NUMBER	TD2018-13-D3045
DATE	10 October 2018



DOWNLOAD LATEST SOFTWARE

Download the latest D3045 software upgrade files from the D3045 product page at nadelectronics.com. The software is downloaded as a zip file.



Unzip the file and the contents will include one or both of the following

- MCU software – filename “d3045m.bin”
- Bluetooth software – filename “d3045bt.bin”

MCU SOFTWARE UPGRADE PROCEDURE

- 1 Save “d3045m.bin” to a USB memory stick.
- 2 With the D3045 unplugged, connect to rear panel SERVICE input port the USB memory stick with “d3045m.bin” already loaded.
- 3 Now, connect the plug to the mains power source.
- 4 The  Standby icon in amber color will flash six times and then the  Standby icon turns into solid amber color.
- 5 Software upgrade is completed. Disconnect the USB memory stick from the rear panel SERVICE input port.

BLUETOOTH SOFTWARE UPGRADE PROCEDURE

- 1 Save “d3045bt.bin” to a USB memory stick.
- 2 With the D3045 unplugged, connect to rear panel SERVICE input port the USB memory stick with “d3045bt.bin” already loaded.
- 3 Now, connect the plug to the mains power source.
- 4 The  Standby icon in bright color will continuously flash for more than 3 minutes until the  Standby icon stops flashing and turns into solid amber color.
- 5 Software upgrade is completed. Disconnect the USB memory stick from the rear panel SERVICE input port.



SOFTWARE UPGRADE PROCEDURE

MODEL NUMBER	D3045
REFERENCE NUMBER	TD2018-13-D3045
DATE	10 October 2018

HOW TO CHECK MCU AND BLUETOOTH SOFTWARE VERSIONS

With the unit at operating mode, press and hold [ON] button of AMP 3 remote control until the display shows the MAIN and BT (Bluetooth) software version details.

RESTORE UNIT TO ITS FACTORY DEFAULT SETTINGS

With the unit at operating mode, press and hold [DIM] button of AMP 3 remote control until "Reset" appears in the display and Source defaults to OPTICAL 1.